



Bearing No.	Boundary dimensions			Basic load ratings(kN)		Limiting speed		Mass
	mm			Dynamic	Static	rpm		
	d	D	B	Cr	Cor	Grease	Oil	
7000AC	10	26	8	4.7	2.1	24,000	32,000	0.019
7001AC	12	28	8	5.1	2.4	22,000	28,000	0.021
7002AC	15	32	9	5.9	3.2	19,000	25,000	0.03
7003AC	17	35	10	6.3	3.6	16,000	22,000	0.04
7004AC	20	42	12	10	5.7	14,000	19,000	0.064
7005AC	25	47	12	11.1	7	12,000	17,000	0.074
7006AC	30	55	13	14.4	9.8	9,500	14,000	0.11
7007AC	35	62	14	17.3	12.1	8,500	12,000	0.15
7008AC	40	68	15	18.7	14.1	8,000	11,000	0.18
7009AC	45	75	16	24.7	19.1	7,500	10,000	0.23
7010AC	50	80	16	25.3	20.5	6,700	9,000	0.25
7011AC	55	90	18	35.5	26.5	6,000	8,000	0.38
7012AC	60	95	18	37	31.3	5,600	7,500	0.4

<b>7013AC</b>	65	100	18	38	33.6	5,300	7,000	0.43
<b>7014AC</b>	70	110	20	45.8	40.9	5,000	6,700	0.6
<b>7015AC</b>	75	115	20	47.5	43.3	4,800	6,300	0.63
<b>7016AC</b>	80	125	22	57.5	51	4,500	6,000	0.85
<b>7017AC</b>	85	130	22	55	52.8	4,300	5,600	0.89
<b>7018AC</b>	90	140	24	71.7	68.7	4,000	5,300	1.15
<b>7019AC</b>	95	145	24	69.8	69.1	3,800	5,000	1.2
<b>7020AC</b>	100	150	24	69	69.7	3,800	5,000	1.25
<b>7021AC</b>	105	160	26	80.9	72.2	3,600	4,800	1.6
<b>7022AC</b>	110	170	28	98.5	93.9	3,400	4,600	1.95
<b>7024AC</b>	120	180	28	103.5	104.5	2,800	3,800	2.1
<b>7026AC</b>	130	200	33	122.4	127.8	2,600	3,400	3.33
<b>7028AC</b>	140	210	33	145.3	152.8	2,400	3,200	3.46
<b>7030AC</b>	150	225	35	174.2	184.9	2,200	3,000	4.8
<b>7032AC</b>	160	240	38	189.6	209	2,000	2,800	5.26