


Stainless Steel Angular Contact Ball Bearing



Номер подшипника	Скважина	Размеры в дюймах				Вместимость (фунты)				Вес в фунтах)
		Внешний диам.	L1	L2	L3	Радиальный		Толкать		
						Статический	Динамический	Статический	Динамический	
SAA10AG0	1.000	1.375	1.14	1.235	1.274	340	194	970	450	0.025
SAA15AG0	1.500	1.875	1.64	1.735	1.774	480	238	1,380	560	0.038
SAA17AG0	1.750	2.125	1.89	1.985	2.024	530	251	1,520	600	0.045
SA020AR0	2.000	2.5	2.186	2.314	2.369	790	405	2,280	960	0.1
SA025AR0	2.500	3	2.686	2.814	2.869	960	459	2,780	1,100	0.12
SA030AR0	3.000	3.5	3.186	3.314	3.367	1,140	507	3,290	1,230	0.14
SA035AR0	3.500	4	3.686	3.814	3.867	1,310	552	3,790	1,350	0.17
SA040AR0	4.000	4.5	4.186	4.314	4.367	1,490	595	4,300	1,470	0.19
SB020AR0	2.000	2.625	2.231	2.393	2.464	1,090	601	3,150	1,380	0.15
SB025AR0	2.500	3.125	2.731	2.893	2.964	1,340	675	3,860	1,590	0.19
SB030AR0	3.000	3.625	3.231	3.393	3.462	1,550	734	4,470	1,750	0.22
SB035AR0	3.500	4.125	3.731	3.893	3.962	1,790	801	5,180	1,930	0.27
SB040AR0	4.000	4.625	4.231	4.393	4.46	2,040	865	5,890	2,100	0.3