


Insocoat Deep Groove Ball Bearing



Подшипник	Размер (мм)			Basic Dynamic Load Rating(KN)		Fatigue Limit Load(KN)	Rated Speed(r/min)	
	д:	Д:	Б:	Динамический	static	Pu[kN]	Reference Speed	Ограничение скорости
6314/C3VL0241	70	150	35	111	68	2.75	9500	6300
6314M/C3VL0241	70	150	35	111	68	2.75	9500	9000
6215/C3VL0241	75	130	25	68.9	49	2.04	10000	6700
6315/C3VL0241	75	160	37	119	76.5	3	9000	5600
6315M/C3VL0241	75	160	37	119	76.5	3	9000	8000
6216/C3VL0241	80	140	26	72.8	55	2.2	9500	6000
6316/C3VL0241	80	170	39	130	86.5	3.25	8500	5300
6316M/C3VL0241	80	170	39	130	86.5	3.25	8500	7500
6217/C3VL0241	85	150	28	87.1	64	2.5	9000	5600
6317/C3VL0241	85	180	41	140	96.5	3.55	8000	5000
6317M/C3VL0241	85	180	41	140	96.5	3.55	8000	7500
6218/C3VL0241	90	160	30	101	73.5	2.8	8500	5300
6318/C3VL0241	90	190	43	151	108	3.8	7500	4800
6318M/C3VL0241	90	190	43	151	108	3.8	7500	7000
6219/C3VL0241	95	170	32	114	81.5	3	8000	5000
6219M/C3VL0241	95	170	32	114	81.5	3	8000	7500
6319/C3VL0241	95	200	45	159	118	4.15	7000	4500
6319M/C3VL0241	95	200	45	159	118	4.15	7000	6300
6220/C3VL0241	100	180	34	127	93	3.35	7500	4800
6320/C3VL0241	100	215	47	182	140	4.75	6700	4300

Insocoat Deep Groove Ball Bearing

6320M/C3VL0241	100	215	47	182	140	4.75	6700	6000
6222/C3VL0241	110	200	38	151	118	4	6700	4300
6222M/C3VL0241	110	200	38	151	118	4	6700	6300
6322/C3VL0241	110	240	50	216	180	5.7	6000	3800
6322M/C3VL0241	110	240	50	216	180	5.7	6000	5300
6224/C3VL0241	120	215	40	153	118	3.9	6300	4000
6324/C3VL2071	120	260	55	216	186	5.7	5600	3400
6324M/C3VL2071	120	260	55	216	186	5.7	5600	5000
6226/C3VL2071	130	230	40	163	132	4.15	5600	3600
6326/C3VL2071	130	280	58	242	216	6.3	5000	3200