


Four point contact ball slewing bearing (with outer flange and internal gear type)



Подшипник		Rothe Erde Model	TG Model	Граничные размеры (мм)				Bolt hole diameter (mm)				Structure dimensions (mm)										Gear Parameters (mm)				Basic load rating Coa (kN)	Вес (кг)
Модель	INA Model			Да	Д:	ди	ЧАС	Ла	Ли	n1	n2	φ1	φ2	Д1	д:	б	час	Б:	С	Ди	да	м	г	делать	Икс		
SLIR15/280				340	216	39	324	252	20	20	M6	M6	310	238	30	5	34	34	279	277	4	56	224		300	10	
SLIR20/414Y	VLI200414N ZT			518	325	56	490	375	8	12	φ18	M12	458.5	350	40	11.5	44.5	47.5	415.5	412.5	5	67	335		600	28.5	
SLIR20/414	VLI 20 0414N ZT RL2			516	325	56	490	375	8	12	φ18	M12	456	350	40	11.5	44.5	47.5	415.5	412.5	5	67	335		300	36.3	
SLIR20/414	VLI200414N			518	325	56	490	375	8	12	18	M12		350	40	8.5	44.5	47.5	415.5	412.5	5	67	335		295	27.5	
SLIR20/414		232.20.0400.013		518	326.5	56	490	375	8	12	18	M12			45.5	10.5	45.5	45.5	415.5	412.5	5	67	335		250	27.1	
SLIR20/414Y		232.20.0400.503		518	326.5	56	490	375	16	12	18	M12			45.5	10.5	45.5	45.5	415.5	412.5	5	67	335		250	26.9	
SLIR20/414Y1		232.21.0475.013		517	326.5	56	490	375	8	12	18	M12			45.5	10.5	45.5	45.5	415.5	411	5	67	335		250	27.1	
SLIR20/414A			1.505.20.00.C	518	326.5	56	490	375	8	12	φ18	M12	453		46	10	46	46	415.5	412.5	5	67	335		500	35.4	
SLIR20/544Y	VLI200544N ZT			648	444	56	620	505	10	16	φ18	M12	588.5		44.5	11.5	44.5	47.5	545.5	542.5	6	76	456		790	40.6	
SLIR20/544Y3	VLI200544N			648	444	56	620	505	10	16	18	M12			44.5	11.5	44.5	47.5	545.5	542.5	6	76	456		385	38	
SLIR20/544Y2		232.20.0500.013		648	445.2	56	620	505	10	16	18	M12			45.5	10.5	45.5	45.5	545.5	542.5	6	76	456		330	36.9	
SLIR20/544Y4		232.20.0500.503		648	445.2	56	620	505	20	16	18	M12			45.5	10.5	45.5	45.5	545.5	542.5	6	76	456		330	36.7	
SLIR20/544Y1		232.21.0575.013		647	445.2	56	620	505	10	16	18	M12			45.5	10.5	45.5	45.5	545.5	541	6	76	456		330	36.9	
SLIR20/544			1.650.20.00.C	648	445.2	56	620	505	10	16	φ18	M12	583		46	10	46	46	545.5	542.5	6	76	456		700	40.2	
SLIR20/644Y	VLI200644N ZT			748	546	56	720	605	12	18	φ18	M12	688.5		44.5	11.5	44.5	47.5	645.5	642.5	6	93	558		900	47.4	
SLIR20/644Y2	VLI200644N			748	546	56	720	605	12	18	18	M12			44.5	8.5	44.5	47.5	645.5	642.5	6	93	558		455	45	
SLIR20/644Y3		232.20.0600.013		748	547.2	56	720	605	12	18	18	M12			45.5	10.5	45.5	45.5	645.5	642.5	6	93	558		390	43.7	
SLIR20/644Y		232.20.0600.503		748	547.2	56	720	605	24	18	18	M12			45.5	10.5	45.5	45.5	645.5	642.5	6	93	558		390	43.4	
SLIR20/644Y1		232.21.0675.013		747	547.2	56	720	605	12	18	18	M12			45.5	10.5	45.5	45.5	645.5	641	6	93	558		390	43.7	
SLIR20/644			1.750.20.00.C	748	547.2	56	720	605	12	18	φ18	M12	683		46	10	46	46	645.5	642.5	6	93	558		780	53.3	
SLIR20/744Y	VLI200744N ZT			848	648	56	820	705	12	20	φ18	M12	788.5		44.5	11.5	44.5	47.5	745.5	742.5	6	110	660		530	54	
SLIR20/744Y3	VLI200744N			848	648	56	820	705	12	20	18	M12			44.5	8.5	44.5	47.5	745.5	742.5	6	110	660		530	51.5	
SLIR20/744Y2		232.20.0700.013		848	649.2	56	820	705	12	20	18	M12			45.5	10.5	45.5	45.5	745.5	742.5	6	110	660		450	51.1	
SLIR20/744Y4		232.20.0700.503		848	649.2	56	820	705	24	20	18	M12			45.5	10.5	45.5	45.5	745.5	742.5	6	110	660		450	50.8	
SLIR20/744Y1		232.21.0775.013		847	649.2	56	820	705	12	20	18	M12			45.5	10.5	45.5	45.5	745.5	741	6	110	660		450	51.1	
SLIR20/744			1.850.20.00.C	848	649.2	56	820	705	12	20	φ18	M12	783		46	10	46	46	745.5	742.5	6	110	660		910	63.1	
SLIR20/844Y	VLI200844N ZT			948	736	56	920	805	14	20	φ18	M12	888.5		44.5	11.5	44.5	47.5	845.5	842.5	8	94	752		1200	65.2	
SLIR20/844Y2	VLI200844N			948	736	56	920	805	14	20	18	M12			44.5	8.5	44.5	47.5	845.5	842.5	8	94	752		600	61.5	
SLIR20/844Y3		232.20.0800.013		948	737.6	56	920	805	14	20	18	M12			45.5	10.5	45.5	45.5	845.5	842.5	8	94	752		510	61.6	
SLIR20/844Y4		232.20.0800.503		948	737.6	56	920	805	28	20	18	M12			45.5	10.5	45.5	45.5	845.5	842.5	8	94	752		510	61.3	